


1. Wiring Diagram.



2. Cable test condition :

Open / Short : 100%

Insulation resistance : 5M ohms

Contact resistance : 2 ohm

Hipot : DC 300V / 1 sec

3. Each pcs with PE polybag.

4	PVC	45P PVC BLACK OVERMOLD	12g	
3	PE	LLDPE 500026 6201	8g	
2	CONN	USB3.0 B/M G/F BLUE	1	P1
1	CABLE	《28AWG (7/0.12TC) *1P+D(7/0.10TC)+AL+M》*2+28AWG (7/0.12TC) *1P+24AWG(7/0.21TC)*2C+A+D+B (96/0.12AM) OD5.5 BLACK	1	1000mm
NO.	PART NO.	DESCRIPTION	QTY	UNIT/REF
		BILL OF MATERIAL		

A	INITIAL RELEASE	2014/08/28	
REV	ECN#	DESCRIPTION	DATE
		P/N: 103-1043-BL-00100	REV A
		TITLE: CABLE 3.0 USB B MALE TO OPEN END	
DRAWN	WENC	DATE	08/24/14
CHECKED	EDWIN	DATE	08/24/14
APPROVAL		CUSTOMER P/N:	
		CUSTOMER:	
		SHEET	1 OF 1